

The RoofClimb Modular Rooftop Ladders provide safe and efficient access to rooftops and elevated surfaces. Designed with modularity in mind, these ladders are shipped as easy-to-assemble kits and bolted together on-site, eliminating the need for welding. This innovative design ensures quick installation, lower shipping costs, and the flexibility to make adjustments as needed. Ideal for a variety of applications, RoofClimb ladders are built to meet safety standards while offering unmatched convenience.

Modular Design: Shipped as kits and bolted together on-site for easy assembly.


No Welding Required: Simplifies installation and allows for quick adjustments.

**Cost-Effective:** Lower shipping costs due to compact, modular packaging.

Flexible: Can be reconfigured or adjusted to fit various rooftop layouts.

Durable: Built with high-quality materials to ensure long-lasting performance.

# MODULAR ROOFTOP LADDERS



# **SPECIFICATIONS**

### Material

| Ladder Rail & Posts | Ø1-1/2" (Ø1.9 OD) Schedule 40 Aluminum Pipe 6061-T6 – 0.97lbs/ft |
|---------------------|--|
| Ladder Components   | High-grade 5000 & 6000 structural aluminum                       |
| Hardware            | All stainless steel  |
| Fittings            | Ø1-1/2" (Ø1.9 OD) Aluminum Magnesium                             |
| End Caps            | Plastic inserts  |
| Finish              | Mill finished (standard); powder coating available               |

### Dimensions

| Rail Spacing            | 24" (610mm)                                       |
|-------------------------|---|
| Overall Width           | 27-3/4" (705mm)                                   |
| Ladder Rail Length      | 10 ft lengths                                     |
| Ladder Rung             | 1-1/4" SQ. 6061-T6, machined serrated top surface |
| Rung Spacing            | 12in (305mm)                                      |
| Rail Extension          | 42" (1067mm) beyond landing surface               |
| Clearance Behind Ladder | 7in (178mm) minimum (vertical position)           |

## Weight

| Ladder Section (10 ft) | 90 lbs (includes rungs, fittings, & hardware)     |
|------------------------|---|
| Cage Section (10 ft)   | 60 lbs (includes hardware)                        |
| Compliance             | Meets/exceeds CAL/WA OSHA, OSHA, & ANSI standards |
| Warranty               | 2 years   |

